



AI-powered ribbon fibre splicer

TYPE-72M12+

Powered by



NanoTune™
Enhanced splice experience

SumiCloud™


Ribbon Splicing. Redefined.




AI-powered,
NanoTune™ for
ribbon splicing



Better fibre
alignment
with ACAS



Patented coatings
on V-grooves
and lens



Versatile,
replaceable
V-grooves

One World, Connected.

Specifications

Items		TYPE-72M12+
Optical fibre requirements	Material	Silica glass
	Profile types	Single/ SMF(G652), MMF(G651), DSF(G653), NZDSF(G655), BIF(G657)
	Fibre count	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12
	Cladding diameter	125µm
	Coating diameter	Single fibre coating dia: 200µm, 250µm, 500µm, 900µm Ribbon fibre thickness: 200-400µm
	Applicable cable	Drop cable(2.0mm×3.1,or2.6mm), Indoor cable(2.0mm×1.6mm)
	Cleave length	10mm
Standard performance	Splice loss (typical) *1	SMF 0.05dB, MMF 0.02dB, DSF 0.08dB, NZDSF 0.08dB
	Splice time (typical)	11sec (SM 12c Quick Mode), 14 sec (SM 12c Std. Mode)
	Heating time (typical)	28sec (FPS-6 sleeves, 40mm 1-12c Quick Mode)
	Splice & heat cycles per battery full charge *2	Approx 180
	Fibre view and magnification	2 CMOS cameras observation, 23X (zoom 46X)
	Proof test	1.96-2.09 N
	Applicable protection sleeve	60mm, 40mm & Sumitomo Electric nano sleeves
Programs	Splice programs	Max 300
	Heating programs	Max 100
Functions	Splice image capture / Splice data storage	200 images / 10,000 splice data (internal memory only) 50,200 images / 20,000 splice data (with 16GB SD card)
	Automatic fibre count detection	Provided
	Automatic arc calibration	Automatically compensates for environmental condition changes
	Auto clamping adjustment system	Provided
	Reversible fibre holder system	Provided
	Dual automatic independent heaters	Provided
	User-selectable heater clamp operation	Provided
	Display of remaining Splice & Heat cycles	Provided (Battery mode)
	Onboard user training video	Provided
	Wireless LAN connectivity (Option) *3	Provided
Size / Weight	Size	128 (W) x 154 (D) x 130 (H) mm (without anti-shock rubber)
	Weight	1.8kg(without Battery) / 2.1kg(with Battery BU-16)
	Monitor	5.0" touch screen color LCD display
Terminals	DC output	DC 12V (for JR-7)
	USB port	USB2.0 (mini-B type)
	Storage media	SD/SDHC memory card MAX32GB
Power supply	AC input	AC 100-240V, 50/60Hz (ADC-16)
	DC input	DC 10-15V, 7.5A
	Battery pack	Li-ion 10.8V, 6400mAh (BU-16)
Operating condition		Altitude : 0-3,660m, Temperature : -10-50°C, Humidity : 0-95%(non-condensing), Wind velocity : up to 15m/sec
Storage condition		Temperature : -40-80°C, Humidity : 0-95%, Battery : -20-30°C(long term)
Electrode life *4		1,500 arc discharges
Software updates		Internet
Data management		Can be stored, edited and analyzed by dedicated PC software

*1 : Average value of the final inspection in room temperature with Sumitomo Electric identical fibre. Measured by cut-back method relevant to ITU-T and IEC standards.

*2 : Splice & Heat cycles may vary depending on the battery status and the operating environment.

*3 : Wireless LAN connectivity is not available in all countries. For more details, please refer to our Web site. <http://global-sei.com/sumitomo-electric-splicers/>

*4 : Achieved in lab condition. Electrode life may vary depending on the operating environment.

Environmental Durability*

	Test details
Shock resistance	Drop from 76cm on 5 faces (excluding top face)
Impact resistance	Equivalent to IK07 on LCD monitor
Water resistance	Equivalent to IPx2
Dust resistance	Equivalent to IP5x

*Splicer operation after shock, impact, water or dust tests, was confirmed under battery power, by Sumitomo Electric.
Does not guarantee the product will not be damaged by these conditions.

Basic Accessories

Product name	Part No.	Qty.
AC adapter	ADC-16 series	1 pc
AC power cord	PC-AC<X>*	1 pc
Cooling tray	—	1 pc
Spare electrode	ER-10	1 pair
Quick reference guide	—	1 pc
Carrying case	CC-72	1 pc
V-groove cleaning brush	VGB-004	1 pc
Hand strap	—	1 pc
USB cable	—	1 pc

*X=2(USA), 3(UE), 4(JP), 5(UK), 6(AUS), 7(South Africa)

Items listed in Basic Accessories are always included with the splicer body. Overall kit content may vary regionally. Please check with your local authorised reseller to confirm kit content in your region.

Accessories

Product name	Part No.	Remarks
SumiCloud card	WLSL series	For SumiCloud™ connection
Battery pack	BU-16	Li-ion 6,400mAh
Battery charger	BC-16	—
Car battery cable	PCV-16	For car battery operation (cigarette socket type)
V-groove cleaning brush	VGB-004	Soft brush for anti-dust coated V-groove

Accessories

Product name	Part No.	Remarks
Fibre holder	FHS-025	For 0.25 mm single fibre
	FHS-09	For 0.9 mm single fibre
	FHM-2	For 2-fibre ribbon
	FHM-3	For 3-fibre ribbon
	FHM-4	For 4-fibre ribbon
	FHM-5	For 5-fibre ribbon
	FHM-6	For 6-fibre ribbon
	FHM-7	For 7-fibre ribbon
	FHM-8	For 8-fibre ribbon
	FHM-9	For 9-fibre ribbon
	FHM-10	For 10-fibre ribbon
	FHM-11	For 11-fibre ribbon
Spare electrode	ER-10	For 250um pitch 12 fibre ribbon
	ER-10-200	For 200um pitch 12 fibre ribbon
Spare V-groove	SVG01-1225	For 250um pitch 12 fibres (ER-10 & FHM-12V included)
	SVG01-1220	For 200um pitch 12 fibres (ER-10-200 & FHM-12N included)
Handheld cleaver	FC-8R-FC	Automatic blade rotation cleaver with cleave counter
	FC-8R-F	Automatic blade rotation cleaver
Table-top cleaver	FC-6R+	Automatic blade rotation cleaver
Fiber Arrangement tool	OFA-02	Glue free fibre arrangement tool
	FTA-02	Glue type fibre rebbonizing tool
Jacket remover	JR-M03	Jacket remover for single fibre
	JR-7	Hot jacket remover for ribbon fibre
Fibre protection sleeve	FPS-1	60 mm sleeve for single fibre
	FPS-40	40 mm sleeve for single fibre
	FPS-5	40 mm sleeve for single fibre and up to 8-fibre ribbon
	FPS-6	40 mm sleeve for single fibre and up to 12-fibre ribbon
	FPS-D60	60 mm sleeve for single-fibre drop, and indoor cables
Alcohol dispenser	HR-3	—



Carrying case with worktable
CC-72



Table-top cleaver
FC-6R+



Hot jacket remover
JR-7



Spare V-groove
SVG01-1225 (for 250um)



Spare V-groove
SVG01-1220 (for 200um)



Pitch changing holder
PCH-12V



Fiber Arrangement tool
OFA-02

Sumitomo Electric Industries, Ltd.