Tel: (818) 998-0223 Fax: (818) 998-6892 sales@AHSystems.com www.AHSystems.com

FCC-1
Tuned Dipole Antenna
25 MHz - 70 MHz

Designed per the FCC specifications, this Tuned Dipole antenna is ideal for site attenuation measurements.





Frequency Range: 25 MHz - 70 MHz

 $\begin{array}{c} \text{Balun Loss: $<$0.5$ dB} \\ \text{Maximum Continuous Power: $300$ Watts} \\ \text{Impedance: $50$ $\Omega$} \end{array}$ 

Connector: N-Type, Female

## **Features**

- F.C.C. Antenna Balun Design
- Omni-directional, Receive and Transmit
- Individually Calibrated (1, 3 and 10 Meter calibration included, horizontal polarization)
- Rugged Construction with low balun loss, low VSWR
- Three Year Warranty

The A.H. Systems FCC-1 Tuned Dipole Antenna is manufactured per ANSI C63.5 (Willmar Roberts design) and covers the 25 MHz – 70 MHz Frequency Range. This half wave dipole antenna provides an accurate standard for precise EMI testing and site attenuation measurements (per EN55022 and ANSI C63.4), and should be considered as a standard reference antenna for frequencies below 1000 MHz.

## **Recommended Accessories**

- ATU-510 (Antenna Tripod, Wooden)
- AEH-510 (Azimuth and Elevation Head)
- PAM-0202 (30 dB Preamplifier)



Tel: (818) 998-0223 Fax: (818) 998-6892 sales@AHSystems.com www.AHSystems.com



